



GRASSPAVE2
BY INVISIBLE STRUCTURES™



GRAVELPAVE2
BY INVISIBLE STRUCTURES™

BASE COURSE DEPTH RECOMMENDATIONS

	NORMAL TRAFFIC		OCCASIONAL PASSES		INFREQUENT PASSES	
	CBR 2-4	CBR >4	CBR 2-4	CBR >4	CBR 2-4	CBR >4
Heavy Fire Truck & H-20 Loading Max 110 psi 80,000 lb	14 in.	12-14 in.	12-14 in.	12 in.	12 in.	10-12 in.
Light Fire Truck & H-15 Loading Typical 85 psi 60,000 lb	12 in.	10-12 in.	10 in.	8-10 in.	8-10 in.	8 in.
Utility & Delivery Truck & H-10 Loading Typical 60 psi 40,000 lb	8-10 in.	8 in.	8-10 in.	6-8 in.	6-8 in.	6 in.
Cars & Pick-Up Truck Access Typical 45 psi 8,000 lb	6-8 in.	6 in.	6 in.	4-6 in.	4-6 in.	2-4 in.
Trail Use and Cart Paths <1,000 lb	2-4 in.	2-4 in.	2-4 in.	0-2 in.	None	None

THESE DEPTH RECOMMENDATIONS SHOULD BE VERIFIED BY THE PROJECT ENGINEER AND LOCAL AUTHORITIES